



- 金屬輕薄高畫質，15 工業液晶，65536 色，1024x768 高解析度 TFT LCD，金屬輕薄外殼，開機 5 秒，通訊反應快速。支援西門子 S7-300 MPI 直接通訊。

■ 產品規格

| 型號 | | GT150-XSD4B | |
|--|--|-----------------------------------|-----------------------------------|
| Display information | | Options | |
| Resolution | 1024x768 dots 15" XVGA TFT LCD | Expansion bus | Optional |
| Colors | 65536 Colors | One stereo speak out | Optional |
| Backlight | LED, 20000 Hrs (note 1) | One MIC in | Optional |
| Display brightness | 350 cd/m ² typical | COM3 / CAN Bus | Optional |
| Dinning | Yes | USB2, USB3 | Optional |
| Technical data | | Front function key | Optional |
| Processor (CPU) | ARM926EJ-S 32bits | 34/40 pin key | Optional |
| Speed | 200 MHz | Ratings | |
| Working memory | 64 MB SDRAM | Power supply voltage | 24 VDC ± 10% |
| Battery backup memory | 128 KB (Optional: 1MB) | Power consumption (max. at 24VDC) | 35W |
| Flash Memory | 8M + 128MB NAND Flash | Net weight | 3.5Kg |
| Operating System | HMI RTOS; PM Designer | Environmental Conditions | |
| Graphic Engine | Support 2D | Operating temperature | 0 to 50 |
| Front panel information (Metal) | | Storage temperature | -20 to 60 |
| Touchscreen Interface | 5 wires analog resistive | Operating and storage humidity | 10%~90%RH none-condensing(note 2) |
| System LED | None | | |
| Communication LED | None | Protection class | NEMA 4 / IP65 (front panel) |
| Interfaces | | Dimensions | |
| Ethernet | 10/100Mb x1 | Faceplate L x W x H | 400 x 298 x 57mm |
| USB | Optional (USB speed host) Optional(USB 2.0 speed Client device) | Cutout A x B | 384.5 x 283mm |
| | | Cutout depth | 40mm |
| Printer port | None | Front panel thickness | 6mm |
| Serial | COM1: RS232/422/485 (DB9 Female) COM2: RS232/485 (5 Pin T.B.) COM3: RS232 (Com1: Pin5;7;8) | | |
| SD | Micro SD Slot | | |

Note 1:the lamp lifetime is the typical value for continuous operation at 25 .

Note 2:10%~90% RH (0~40),10%~55% RH (41 ~50), Contamination degree 2