

特點

- Hing reliability, long life.
- Safety.
- Low input power consumption.
- No contact points.
- No switching sparks.
- No noise.
- No mechanical damage.



1.選購型號 : TB-RK-4 □ □ - □ □

NO	Output Current	NO	Input Voltage	NO	Output Voltage	NO	Port
4	4A	D	DC 3~32V	D	DC 3~60V	1	One
		A	AC 80~280V	A	AC 24~280V	2	Two
						4	Four
						8	Eight

2.主要規格

Type	TB-RK-4DA	TB-RK-4DD	TB-RK-4AD
Max load current	4A	4A	4A
Max 1-cycle peak surge	50A	8.5A	8.5A
Control voltage range	3 ~ 32 VDC	3 ~ 32 VDC	80 ~ 280 VAC
Must turn off voltage	MAX 1.0 VDC	MAX 1.0 VDC	MAX 10 VAC
Load voltage range	24~280 VAC	3 ~ 60 VDC	3 ~ 60 VDC
Min blocking voltage	600 VAC	80 VDC	80 VDC
Max off-state leakage	Less 5 mA	Less 1 mA	Less 1 mA
Dielectric strength input-output	4000 VACrms	2500 Vrms	2500 Vrms
Turn off time	LESS 1/2 AC cycle	LESS 1/2 cycle	LESS 1/2 See
Max off-state dv/dt	100 V/μ SEC	200 V/μ SEC	
Max on-state voltage drop	2.0 VAC	1.2 Vrms	
Input impedance	1.5 Kohm		
Isolate impedance	10 ⁹ ohm		
Frequency range	47 ~ 70 Hz		
Turn on time	Less 2 mSec		
Capacitance in-out	Less 15 PF		

3.外觀尺寸 (Unit:mm)

Type	Dimension (LxWxH)mm
TB-RK-4□□-2	34x85x51
TB-RK-4□□-4	62.5x85x51
TB-RK-4□□-8	123.5x85x51

