

特點/Features

- 材質：中碳鋼/S45C
- 緩衝材：工程塑膠，適用溫度環境：-30~80
Buffer Material :Engineering class Plastic
- 固定方式：止付螺絲固定式/Fixed mode : Set screw type
- 高扭力/High torque.
- 高剛性/High rigid.
- 抗震佳/Great shock resistance
- 適合用於一般傳動機構及切削機構
Suitable for general transmission、high inertia and cutting mechanism.



選購型號/Order NO.

CS-RJS- \square - \square X \square

(øD) (ød1) (ød2)

NO.	外徑/Diameter	NO.	孔徑/Aperture(Min)	NO.	孔徑/Aperture(Max)
80	ø 80mm	38	ø 38mm	45	ø 45mm

規格/Specifications

TYPE	Rated Torque 一般扭力 (N.m)	Max. Torque 最大扭力 (N.m)	Max. Rotational Frequency 最高回轉數 (Rpm/min)	Moment* of Inertia 慣性 (kg · m ²)	Errors of Eccentricity 容許偏心 (mm)	Errors of Angularity 容許偏角 (°)
CS-RJS-80-RD	600	1200	6000	48.57x10	0.10	2

外型尺寸/Dimensions (Unit:mm)

TYPE	D	I	L	E	F	G	M	d1xd2 標準孔徑 公差(H8)		Mass* 質量(g)
								Min	Max	
CS-RJS-80-RD	80	45	114	18	3	15	M8	38	45	3800

