

特點/Features

- 材質：鋁合金/Aluminum alloy
- 表面處理：陽極處理/Anodizing standard white
- 緩衝材：不銹鋼彈片/Buffer Material : SUS disk.
- 固定方式：夾緊式/Fixed mode : Clamp type.
- 扭力大/High torque. ● 低慣性/Low inertia.
- 高剛性/High rigid. ● 零背隙/Zero backlash.
- 適合用於工作母機、伺服馬達、高精度傳動/
Suitable for working machine、servomotor and high precision.



選購型號/Order NO.

CS-GS- C - x

(øD)		(ød1)		(ød2)					
NO.	外徑/Diameter	NO.	外徑/Diameter	NO.	孔徑/Aperture(Min)	NO.	孔徑/Aperture(Max)	NO.	孔徑/Aperture(Max)
27	ø27mm	57	ø57mm	5	ø5mm	10	ø10mm	25	ø25mm
34	ø34mm	65	ø65mm	6	ø6mm	14	ø14mm	28	ø28mm
40	ø40mm			8	ø8mm	16	ø16mm		
45	ø45mm			10	ø10mm	19	ø19mm		
50	ø50mm			12	ø12mm	22	ø22mm		

規格/Specifications

TYPE	Rated Torque 一般扭力 (N.m)	Max. Torque 最大扭力 (N.m)	Max. Rotational Frequency 最高回轉數 (Rpm/min)	Moment* of Inertia 慣性 (kg m ²)	Errors of Eccentricity 容許偏心 (mm)	Errors of Shaft End-Play 容許軸向位差 (mm)	Errors of Angularity 容許偏角 (°)
CS-GS-27C	1.5	3	10000	2.5x10 ⁻⁶	0.02	±0.15	1.0
CS-GS-34C	6	12	10000	8.2x10 ⁻⁶	0.02	±0.20	1.0
CS-GS-40C	7	14	10000	19.0x10 ⁻⁶	0.02	±0.25	1.0
CS-GS-45C	10	20	10000	29.7x10 ⁻⁶	0.02	±0.30	1.0
CS-GS-50C	17	34	10000	75.0x10 ⁻⁶	0.02	±0.30	1.0
CS-GS-57C	25	50	10000	100.0x10 ⁻⁶	0.02	±0.40	1.0
CS-GS-65C	25	110	10000	250.0x10 ⁻⁶	0.02	±0.40	1.0

外型尺寸/Dimensions (Unit:mm)

TYPE	D	I	F	L	H	M	d1xd2 標準孔徑 公差(H7)		Mass* 質量(g)
							Min	Max	
CS-GS-27C	27	10.5	2.5	23.5	9.0	M3	5	10	30
CS-GS-34C	34	12.0	3.0	27.0	12.0	M3	6	14	48
CS-GS-40C	40	15.0	4.5	34.5	14.0	M4	8	16	93
CS-GS-45C	45	15.0	5.0	34.5	16.0	M4	10	19	110
CS-GS-50C	50	20.0	6.0	46.0	18.0	M5	10	22	215
CS-GS-57C	57	20.0	6.0	46.0	21.0	M5	12	25	240
CS-GS-65C	65	24.0	7.0	55.0	25.0	M6	12	28	445

