



ELECTRICAL SPEC.

Detection System	Incremental 增量型
Output Wave 輸出波形	Square Wave 方波
Standard Number of Pulse Per Revolution 解析	5, 10, 20, 30, 40, 50, 60, 80, 100, 120, 150, 180, 200, 250, 300, 360, 400, 500, 600, 720, 800, 900, 1000, 1024, *1800, 2000, *2048, 2500, *3000, *3600, *4000, *4096, *5000 *only with AB phase
Output Phase 輸出相	AB phase or ABZ phase
Electronics 電路特性	NPN Voltage, NPN Open Collector, Push Pull or Line Driver
Power Supply 供應電源	DC 8~26V, DC 5V fixed
Current Consumption 消耗電流	≤ 60 mA
Output Capacity 輸出容量	Sync. Current: 20 mA, Residual Voltage: 0.5V or less
Max. Response 最大響應頻率	10K Hz ~ 100K Hz
Phase Different 相位差	A, B phase different 90°±45° (T/4±T/8), Z phase T±T/2
Wave Form Rise / Fall 波形上下時間	2 μs or less
Polarity 極性保護	Aganst Reverse Protection (not with DC 5V)

MECHANICAL SPEC.

Shaft Diameter 軸徑	10 mm
Shaft Loading 軸荷重	(10 ~ 1000 PPR) Axial 軸向: 5 Kg, Radial 徑向: 10 Kg (over 1000 PPR) Axial 軸向: 3 Kg, Radial 徑向: 6 Kg
Starting Torque (at 25°C) 起動轉矩	Without shaft seal: 260 gf-cm or less; With shaft seal: 400 gf-cm or less
Max. Speed 最大機械容許速度	6,000 rpm; 2,000 rpm for IP 65
Vibration 震動	10g (10±1,500 Hz)
Shock 衝擊	20g per 11 ms
Cable 電線	Ø5.4, 100 cm long
Weight 重量	≤ 500g

ENVIRONMENTAL SPEC.

Operating Temp. / Humidity 操作溫度/濕度	-10°C ~ 60°C, RH 35% ~ 90% (No Condensation)
Storage Temp. 儲存溫度	-20°C ~ 80°C
Protection 保護等級	IP64 (standard): Dust & Dripping proof; IP65 (option):with shaft seal

ORDERING INFORMATION

EHP-N6A

Pulse per Revolution
解析

5, 10, 20, 30, 40, 50, 60, 80, 100,
120, 150, 180, 200, 250, 300, 360,
400, 500, 600, 720, 800, 900, 1000,
1024, *1800, 2000, *2048, 2500,
*3000, *3600, *4000, *4096, *5000 P/R
*only with AB phase

Output Phase
輸出相

2: AB phase
3: ABZ phase
4: AB+Z high phase

Electronics
電路特性

Blank: NPN Voltage
C: NPN Open Collector
PP: Push Pull
*L: Line Driver 5 Vdc
*HL: Line Driver 5~26 Vdc

Supply Voltage
供應電源

Blank: 8~26 Vdc
5V: 5 Vdc fixed

Connection
連接器

Blank: Axial Cable
*R7: Radial 7 pin
*R10: Radial 10 pin

Protection
保護等級

Blank: IP64
*K1: IP65