

**ELECTRICAL SPEC.**

Detection System	Incremental 增量型
Output Wave 輸出波形	Square Wave 方波
Stroke (mm) 量測行程	200, 500, 1000
Standard Resolution (mm/pulse) 解析	1, 0.5, 0.2, 0.1, 0.04
Accuracy 精度	± 0.05% FS, ±1 count
Output Phase 輸出相	AB phase or ABZ phase
Electronics 電路特性	NPN Voltage, NPN Open Collector, Push Pull or Line Driver
Power Supply 供應電源	DC 8~26V, DC 5V fixed
Current Consumption 消耗電流	≤ 60 mA
Output Capacity 輸出容量	Sync. Current: 20 mA, Residual Voltage: 0.5V or less
Max. Response 最大響應頻率	10K Hz ~ 100K Hz
Phase Different 相位差	A, B phase different 90°±45° (T/4±T/8), Z phase T±T/2
Wave Form Rise / Fall 波形上下時間	2 μs or less
Polarity 極性保護	Against Reverse Protection (not with DC 5V)

**MECHANICAL SPEC.**

Wire specification 線徑規格	Material: SUS304 with nylon coating Diameter: 0.6 mm; Breaking load: 16 Kg
Max. Travel Speed 最大往復速度	1,000 mm / sec.
Vibration 震動	10g (10±1,500Hz)
Shock 衝擊	20g per 11 ms
Cable 電線	Ø4.5 50 cm long
Weight 重量	< 450g
Starting Torque on Spring 拉力	Max 700g

**ENVIRONMENTAL SPEC.**

Operating Temp. / Humidity 操作溫度/濕度	0°C ~ 60°C, RH 35% ~ 90% (No Condensation)
Storage Temp. 儲存溫度	-20°C ~ 80°C
Protection 保護等級	IP50 : Dust Proof (only for encoder housing)
Life 壽命	Typical > 1 X 10 <sup>6</sup> cycles

**ORDERING INFORMATION**

<b>EHL-SS</b>	Measuring Range 量測行程	Resolution 解析	Output Phase 輸出相	Electronics 電路特性	Supply Voltage 供應電源
	02: 200 mm 05: 500 mm 10: 1000 mm	1: 1 mm 05: 0.5 mm 02: 0.2 mm 01: 0.1 mm 004: 0.04 mm	Blank: AB phase *Z: ABZ phase	Blank: NPN Voltage C: NPN Open Collector PP: Push Pull *L: Line Driver 5 Vdc *HL: Line Driver 5~26 Vdc	Blank: 8~26 Vdc 5V: 5 Vdc fixed