

Modbus RTU : N,8,1

Read03/Write06

Address(HEX)	Parameter	Coding and Range
0000	Type	0:J, 1:K, 2:T, 3:E, 4:B, 5:R, 6:S, 7:N, 8:C, 9:DPT, A:mV, B:Voltage, C:Current; D:RSP
0001	Unit	0:dC, 1:dF, 2:ENG
0002	Dp	附件一
0003	LoLt	附件二
0004	HiLt	附件二
0005	Offset	附件二
0006	SCAL	4位(-1999 ~ 9999), 3位(-199 ~ 999)
0007	SCAH	4位(-1999 ~ 9999), 3位(-199 ~ 999)
0008	Filter	0~999
0009	dir	0:0/4~20mA, 1:20~0/4mA
000A	cut	0:None, 1:Lo, 2:Hi, 3:HiLo
000B	LoCaData1	0~32767
000C	HiCaData1	0~32767
000D	ID	1~255
000E	BR	0:2400, 1:4800, 2:9600, 3:19200
000F	A1FU	0:None, 1:Hi, 2:Lo
0010	A1MD	0:None, 1:Stdy, 2:Lath, 3:St.la
0011	A1SP	4位(-1999 ~ 9999), 3位(-199 ~ 999)
0012	A1HY	4位(-1999 ~ 9999), 3位(-199 ~ 999)
0013	A2FU	0:None, 1:Hi, 2:Lo
0014	A2MD	0:None, 1:Stdy, 2:Lath, 3:St.la
0015	A2SP	4位(-1999 ~ 9999), 3位(-199 ~ 999)
0016	A2HY	4位(-1999 ~ 9999), 3位(-199 ~ 999)
0017	MVL	4位(-19.99 ~ 60.00), 3位(-19.9 ~ 60.0)
0018	MVH	4位(-19.99 ~ 60.00), 3位(-19.9 ~ 60.0)
0019	VL	4位(-10.00 ~ 10.00), 3位(-10.0 ~ 10.0)
001A	VH	4位(-10.00 ~ 10.00), 3位(-10.0 ~ 10.0)
001B	MAL	4位(0.00 ~ 24.00), 3位(0.0 ~ 24.0)
001C	MAH	4位(0.00 ~ 24.00), 3位(0.0 ~ 24.0)
1002	PV	4位(-1999 ~ 9999), 3位(-199 ~ 999); Type=RSP時才能寫入
1006	LED	BIT 1, 0 (A2, A1)

附件一
4位顯示

Type	Dp
TC-J	0~1
TC-K	0~1
TC-T	0~1
TC-E	0~1
TC-B	0~1
TC-R	0~1
TC-S	0~1
TC-N	0~1
TC-C	0~1
DPT	0~1
mV	0~3
Voltage	0~3
Current	0~3
RSP	0~3

3位顯示

Type	Dp
TC-J	0~1
TC-K	0~1
TC-T	0~1
TC-E	0~1
TC-B	0~1
TC-R	0~1
TC-S	0~1
TC-N	0~1
TC-C	0~1
DPT	0~1
mV	0~2
Voltage	0~2
Current	0~2
RSP	0~2

附件二
4位顯示

Type	Measuring Range		Offset	Unit
	LL	UL		
TC-J	-50	1000	±52	°C
TC-K	-50	1370	±71	°C
TC-T	-270	400	±33	°C
TC-E	-50	700	±37	°C
TC-B	0	1750	±87	°C
TC-R	-50	1750	±90	°C
TC-S	-50	1750	±90	°C
TC-N	-50	1300	±67	°C
TC-C	-50	1800	±92	°C
DPT	-200	850	±52	°C
mV	-1999	9999	±59	ENG
Voltage	-1999	9999	±59	ENG
Current	-1999	9999	±59	ENG
RSP	-1999	9999	±59	ENG

3位顯示

Type	Measuring Range		Offset	Unit
	LL	UL		
TC-J	-50	999	±52	°C
TC-K	-50	999	±71	°C
TC-T	-199	400	±33	°C
TC-E	-50	700	±37	°C
TC-B	0	999	±87	°C
TC-R	-50	999	±90	°C
TC-S	-50	999	±90	°C
TC-N	-50	999	±67	°C
TC-C	-50	999	±92	°C
DPT	-199	850	±52	°C
mV	-199	999	±59	mV
Voltage	-199	999	±59	V
Current	-199	999	±59	mA
RSP	-199	999	±59	ENG

4位顯示

Type	Measuring Range		Offset	Unit
	LL	UL		
TC-J	-58	1832	±94	°F
TC-K	-58	2498	±127	°F
TC-T	-454	752	±60	°F
TC-E	-58	1292	±67	°F
TC-B	32	3182	±157	°F
TC-R	-58	3182	±162	°F
TC-S	-58	3182	±162	°F
TC-N	-58	2372	±121	°F
TC-C	-58	3272	±166	°F
DPT	-328	1562	±94	°F

3位顯示

Type	Measuring Range		Offset	Unit
	LL	UL		
TC-J	-58	999	±94	°F
TC-K	-58	999	±127	°F
TC-T	-199	752	±60	°F
TC-E	-58	999	±67	°F
TC-B	32	999	±157	°F
TC-R	-58	999	±162	°F
TC-S	-58	999	±162	°F
TC-N	-58	999	±121	°F
TC-C	-58	999	±166	°F
DPT	-199	999	±94	°F